

## Key Features

Amazing color accuracy | Smart design | Enhanced sound



## Product Description

The ViewSonic® LightStream™ PJD5353LS price-performance short throw projector features 3,200 lumens, native XGA 1024 x 768 resolution, user-friendly design, and a sleek white chassis. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment, while SonicExpert™, ViewSonic’s proprietary sound enhancement technology, powers a 2W speaker to deliver incredibly clear and audible sound. A short throw lens with a 0.6 throw ratio offers large projection images for smaller rooms. The PJD5353LS also features HDMI and VGA connectivity, and a RS232 control port. An energy-saving DynamicEco® feature reduces power consumption by up to 70%, and extends the lamp life up to 10,000 hours\*\*. With advanced audiovisual features, flexible connectivity options, and an affordable price, the PJD5353LS is ideal for use in education and small business environments.




- |                     |                 |                   |                           |
|---------------------|-----------------|-------------------|---------------------------|
| 1. IR remote sensor | 5. HDMI         | 9. VGA (x2)       | 13. USB type Mini B       |
| 2. Projection lens  | 6. Video In     | 10. Control Panel | 14. Kensington® Lock Slot |
| 3. Elevation foot   | 7. Audio In/Out | 11. Monitor Out   |                           |
| 4. Focus ring       | 8. AC In        | 12. RS232         |                           |



1024 x 768  
**RESOLUTION**



3,200  
**LUMENS**



0.61  
**THROW RATIO**

### Contact Sales

- call: 888.881.8781
- email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)
- visit: [viewsonic.com](http://viewsonic.com)

**Display:**

|                                              |                                                                |
|----------------------------------------------|----------------------------------------------------------------|
| Type:                                        | DLP                                                            |
| Resolution Type:                             | XGA                                                            |
| Resolution:                                  | 1024 x 768                                                     |
| Brightness (ANSI Lumens):                    | 3,200                                                          |
| Throw Distance:                              | 2.0 – 10.12 ft. / 0.61 – 3.09 m                                |
| Throw Ratio:                                 | 0.61                                                           |
| Display Size (in.):                          | 50 - 250 in. / 1.27 - 6.35 m                                   |
| Keystone:                                    | Manual vertical digital keystone correction ( $\pm 40^\circ$ ) |
| Lens:                                        | Fixed zoom / manual optical focus                              |
| Light Source (watt):                         | 190                                                            |
| Light Source Life, Normal (hours):           | 5000                                                           |
| Light Source Life, Dynamic Eco-Mode (hours): | 10000                                                          |
| Color Depth:                                 | 30 bits, 1.07B Color (10+10+10)                                |
| Dynamic Contrast Ratio:                      | 22000:1                                                        |
| Aspect Ratio:                                | 4:3 (native)                                                   |

**Video Signal:**

|                       |           |
|-----------------------|-----------|
| Frequency Horizontal: | 15–102KHz |
| Frequency Vertical:   | 23–120Hz  |

**Compatibility:**

|                        |             |
|------------------------|-------------|
| PC Resolution (max):   | 1920 x 1080 |
| Mac® Resolution (max): | 1920 x 1080 |

**Connector:**

3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS-232)(1), HDMI 1.4(1), VGA In(2), VGA Out(1), Composite RCA Video In(1), S-Video In(1), Mini USB(1), RGB Input(15-pin mini D-Sub (x2))

**Audio:**

|                    |    |
|--------------------|----|
| Internal Speakers: | 2W |
|--------------------|----|

**Power:**

|                    |                                                  |
|--------------------|--------------------------------------------------|
| Voltage:           | 100~240VAC (Auto Switching), 50-60Hz (universal) |
| Consumption (max): | 265W                                             |
| Stand-by:          | <0.5W                                            |

**Controls:**

|                    |                                                                                                                                 |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Physical Controls: | Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source                               |
| On Screen Display: | Display, Picture, Source, System Setup (Basic), System Setup (Advanced), Information(See user guide for full OSD functionality) |

**Operating Conditions:**

|                            |                     |
|----------------------------|---------------------|
| Temperature:               | 32-104° F (0–40° C) |
| Humidity (non-condensing): | 10-90%              |

**Noise Level:**

|           |      |
|-----------|------|
| Normal:   | 32dB |
| Eco-Mode: | 27dB |

**Weight (imperial):**

|              |     |
|--------------|-----|
| Gross (lbs): | 8.4 |
|--------------|-----|

**Weight (metric):**

|                         |     |
|-------------------------|-----|
| Net Without Stand (kg): | 2.5 |
| Gross (kg):             | 3.8 |

**Dimensions (imperial) (WxHxD):**

|                               |                     |
|-------------------------------|---------------------|
| Packaging (in.):              | 16.0 x 8.85 x 13.58 |
| Physical Without Stand (in.): | 12.44 x 8.98 x 4.08 |

**Dimensions (metric) (WxHxD):**

|                              |                   |
|------------------------------|-------------------|
| Packaging (mm):              | 408 x 225 x 345   |
| Physical Without Stand (mm): | 316 x 228 x 103.7 |

**General:**

Regulations: CB, TUV-GS, UL/cUL, FCC (including ICES-003), CE, C-Tick, Mexico Energy, EAC, UkrSEPRO/EMC DOC, UL COC, TUV-S, PSB, KCC, KC, SASO, CCC, BIS, WEEE, RoHS, REACH, SVHC, ErP

PACKAGE CONTENTS: PJD5353LS projector, power cable, VGA cable, remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide)

Warranty: 2-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service\*\*

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907808018

**Accessories:**

PJ-IWBADP-003, PJ-VTOUCH-10S, PJ-WMK-601, PJ-WMK-601-S, RLC-092