


Key Features

Full HD 1080p, 3200 Lumens | Amazing color accuracy | Enhanced 10W speaker | Smart design



Product Description


The ViewSonic LightStream® PJD7720HD Full HD projector features 3,200 lumens, Full HD 1920x1080 native resolution, an intuitive, user-friendly design and a sleek black chassis. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment, while SonicExpert™, ViewSonic's proprietary sound enhancement technology, powers a 10W speaker to deliver incredibly clear and audible sound. PortAll™ - a neatly designed and enclosed HDMI/MHL connection compartment, supports wireless HDMI dongles or MHL connectors, while a cable management hood eliminates unsightly cable clutter. With a smart design, the PJD7720HD is the ideal projector for high definition presentations.



1920 x 1080
RESOLUTION



3,200
LUMENS



1.49~1.64:1
THROW RATIO

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Type:	DLP
Resolution Type:	1080p
Resolution:	1920 x 1080
Brightness (ANSI Lumens):	3,200
Throw Distance:	3.25 – 35.73 ft. / 1.0 – 10.9 m
Throw Ratio:	1.49~1.64:1
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m
Lens:	1.1x Manual optical zoom / manual optical focus
Light Source (watt):	210
Light Source Life, Normal (hours):	4000
Light Source Life, Dynamic Eco-Mode (hours):	10000
Color Depth:	30 bits, 1.07B Color (10+10+10)
Dynamic Contrast Ratio:	22000:1
Aspect Ratio:	16:9

Video Signal:

Frequency Horizontal:	15–100KHz
Frequency Vertical:	24–120Hz

Compatibility:

PC Resolution (max):	Up to 1920x1080 non-interlaced
Mac® Resolution (max):	Up to 1920x1080 (may require MAC adapter)

Connector:

3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS-232)(1), HDMI 1.4(1), HDMI MHL(1), Mini USB(1)

Audio:

Internal Speakers:	10W
--------------------	-----

Power:

Voltage:	100~240VAC (Auto Switching), 50-60Hz (universal)
Consumption (max):	330W
Stand-by:	<0.5W

Controls:

Physical Controls:	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display:	Display, Picture, Source, System Setup (Basic), System Setup (Advanced), Information (See user guide for full OSD functionality)

Operating Conditions:

Temperature:	32-104° F (0-40° C)
Humidity (non-condensing):	10-90%

Noise Level:

Normal:	35dB
Eco-Mode:	30dB

Additional Hardware:

Kensington Lock Slot:	1
-----------------------	---

Weight (imperial):

Net (lbs):	5.3
Gross (lbs):	8.4

Weight (metric):

Net (kg):	2.4
Gross (kg):	3.8

Dimensions (imperial) (WxHxD):

Packaging (in.):	16.14 x 8.86 x 17.72
Physical (in.):	12.44 x 8.98 x 4.08

Dimensions (metric) (WxHxD):

Packaging (mm):	410 x 225 x 450
Physical (mm):	316 x 228 x 103.7

General:

Regulations: Mexico Energy test/Registration, EAC, TUV-S Mark (Argentina), India BIS, FCC, CE EMC, CB, CCC, RoHS, REACH, SVHC, WEE, ErP, Mexico NOM, cTUVus, RCM, PSB, KC

PACKAGE CONTENTS: PJD7720HD projector, power cable, remote control (batteries included), Quick Start Guide, ViewSonic Wizard CD (with User Guide)

Warranty: 2-year limited warranty on parts and labor, 1-year limited warranty on lamp

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907845617

Accessories:

PGD-350, PJ-CASE-009, PJ-CM-001, PJ-SCW-1001W, PJ-WMK-006, RLC-100, WPG-300